



## ATEX PU TAG 34 MM READ-WRITE



<b>Description:</b>	Configurable ATEX PU 34 mm TAG with 2048 bits read-write memory		
<b>IC type:</b>	HITAG S		
<b>Physical:</b>	Diameter:	34.20 mm	± 0.30 mm
	Thickness:	08.00 mm	± 0.20 mm
	Hole:	05.20 mm	± 0.10 mm
	Weight:	07.00 g	± 1.00 g
	Material:	PA6 / PU	Black
<b>Electrical:</b>	Operating Frequency:	125 kHz	± 6 kHz
<b>Thermal:</b>	Operating temperatures:	-45°C up to 60°C	
<b>Chemical:</b>	Water immersion IP67		
	Aqueous solution of salts		
	Unleaded gasoline		
	Petroleum		
	Mineral and vegetable oil		
<b>EX Marking:</b>	BVS 05 ATEX E 092 Ⓜ II 2G EEx ia IIC T4 CE <sup>0158</sup> Ⓜ I M2 EEx ia I Ⓜ II 2 D Ex iaD 21 T70 °C -45°C ≤ Ta ≤ 60°C		
<b>Special:</b>	Upon request other colours are available (Black, Blue, Red, Green) Upon request other chip technologies are available.		
<b>Part number:</b>	TID-TP-PU30RW		