



## TEC PU TAG 54 MM I-CODE SLI SL2

<b>Description:</b>	TEC PU 54 mm TAG I-Code SLI SL2		
<b>IC type:</b>	I-Code SLI SL2 ICS20 128 byte ISO 15693		
<b>Physical:</b>	Diameter:	54.00 mm	± 0.50 mm
	Thickness:	15.00 mm	± 1.00 mm
	Hole:	06.20 mm	± 0.10 mm
	Weight:	45.00 g	± 3.00 g
	Material:	PU	Black
<b>Electrical:</b>	Operating Frequency:	13.56 MHz	
<b>Thermal:</b>	Storage temperatures:	-40°C up to 95°C	
	Operating temperatures:	-40°C up to 85°C	
<b>Chemical:</b>	Water immersion IP67		
	Aqueous solution of salts		
	Unleaded gasoline		
	Petroleum		
	Mineral and vegetable oil		
<b>Special:</b>	Upon request other colours are available. Upon request other chip technologies are available.		
<b>Part number:</b>	TAK-15-AA		

© TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.