

**Rugged PDA with 125 kHz RFID Reader and WLAN, Bluetooth, IRDA**



**TRISP-LF  
ATEX Zone 2**



<b>Description:</b>	Rugged IPDA with integrated 125 kHz RFID Reader/Writer	
<b>Processor:</b>	400 Mhz Intel Xscale PXA255	
<b>Software:</b>	Pocket PC 2003	
<b>Housing:</b>	Anti-static non-corrosive IP 65	Fall protection min.1 m on concrete
<b>Display:</b>	TFT 3.5 Zoll,64 colours, resolution 320x240 pixel	
<b>Memory:</b>	64 MB SDRAM, 32 MB ROM, 2,8 MB NVRAM	
<b>Power Supply:</b>	1800 mAh Lithium-Ion	
<b>Dimensions/Weight:</b>	224 x 89 x 49 mm / 800 g	
<b>RFID Unit:</b>	125 Khz Read and Write	
<b>Temperature:</b>	-10°C.....+60°C	
<b>Supported transponders:</b>	EM410x, Q5, HITAG S (32/256/2 kbit), ISO 11784/5 FDX-B	Other on request
<b>Interfaces:</b>	WLAN IEEE 802.11b, Bluetooth I.I Class 2 IRDA I.I (115,2 KB/s)	
<b>Technical certifications:</b>	Ex-designation: II 3G EEx nL IIC T6 II 3D T95°C IP65 ZELM 04 ATEX 3201 CE 0470	
<b>Part number:</b>	TRISP-LF-Zone2	

© TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.